


D3036 SERIES **Overhead Adjustable Size3-6 Door Closers**




STANDARD FEATURES

- **Certification:** CE Marked
- **Spring Power:** Adjustable Size 3-6
- **Durability:** 500,000 cycles above
- **Function:** Adjustable Closing speed
Adjustable Latching speed
Backcheck Optional
Delay Action Optional
- **Arm type:** Detachable
- **Max. Opening:** 180 °(Fig1, Fig66, Fig61)
- **Fitting Application:** Fig1, Fig66, Fig61, Figure 66 achieved by separate parallel arm bracket offered as optional accessory
- **Mechanism:** Rack & Pinion
- **Materials of Body:** Die-cast Aluminum
- **Tested to EN1154:** Yes
- **Tested to EN1634:** Yes
- **CE Marked:** Yes
- **EN1154 Classification:** 4 8 3/6 1 1 3(Fig1, Fig61)
4 8 2/4 1 1 3(Fig66)
- **Door width (max.):** 1500mm
- **Door weight (max.):** 150kgs
- **Application:** Suitable for interior wood, hollow metal, and aluminum doors and frames
- **Product Description:** Efficient cam and roller design
- **Finish:** Silver, Brown, White, Black, Others upon request.
- **Warranty:** 5 Years
- **Cross reference:** Dorma TS83


AVAILABLE INSTALLATION TYPE:




1 Standard installation




2 Frame installation




3 Parallel arm installation
 (The above bracket is supplied with every TS 83 standard doorcloser.)




4 Hold-open arm installation
 Adjustable for hold-open up to 150°. Can be switched off to act as a standard arm.




5 Soffit bracket and arm for standard installation with shaped architrave



6 Parallel arm bracket with upstand



7 Angle bracket installation
 Frame installation for outward opening doors with extra deep reveals.



8 Drop plate installation
 For installation on frame (or door) when direct fixing of closer is not possible.

Model #	Spring power	Recommended Door Weight	Recommended Max. Door Leaf Width (mm)	Notes
D3036	3-6#	60-150KGS	950-1500 mm	Sliding track arm optional

PRODUCT DIMENSIONS:

